

TR 136 - Specifiche tecniche



Description

TR 136 è stato sviluppato da BKT per l'utilizzo con trattori e rimorchi nelle operazioni di lavorazione della terra e di trasporto. Lo pneumatico assicura trazione superiore in tutte le condizioni operative insieme ad un'ottima resistenza ad ogni tipo di taglio, riducendo il tempo di fermo macchina ed incrementando la vostra produttività. Grazie al numero maggiore di ramponi, TR 136 assicura straordinaria trazione anche con carichi elevati.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore • Rimorchio

Version	STANDARD
Type	TT
Tyre Size	16.9 - 30 (14 - 30)
LI/SS	143 A8

Dimensions US Standard

Usa code	94044108
Ply Rating	14
Section Width (inch)	16.9
Overall Diameter (inch)	58.5
Static Loaded Radius (inch)	26.7
Rolling Circumference (inch)	175.4
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-005243
TRA Code	R1

Load capacity (lbs)

mph / psi	40
25	6000

Printed on 19/04/2024 17:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..