

## TR 136 - Specifiche tecniche



### Description

TR 136 è stato sviluppato da BKT per l'utilizzo con trattori e rimorchi nelle operazioni di lavorazione della terra e di trasporto. Lo pneumatico assicura trazione superiore in tutte le condizioni operative insieme ad un'ottima resistenza ad ogni tipo di taglio, riducendo il tempo di fermo macchina ed incrementando la vostra produttività. Grazie al numero maggiore di ramponi, TR 136 assicura straordinaria trazione anche con carichi elevati.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore • Rimorchio

Version	STANDARD
Type	TL
Tyre Size	18.4 - 26
LI/SS	150 A6

## Dimensions International Standard

<b>Ply Rating</b>	14
<b>Section Width (mm)</b>	480
<b>Overall Diameter (mm)</b>	1450
<b>Static Loaded Radius (mm)</b>	646
<b>Rolling Circumference (mm)</b>	4205
<b>SRI (mm)</b>	675
<b>Rim Rec</b>	W 16 L
<b>Rim Alt</b>	W 15 L
<b>ECE</b>	E4-106R-002301
<b>TRA Code</b>	R1

## Load capacity (Kg)

km/h / bar	2.60
30	3350

Printed on 19/04/2024 20:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..