

TR 144 - Specifiche tecniche



Description

TR 144 è idoneo per essere utilizzato con trattorini nelle operazioni per la lavorazione della terra. TR 144 garantisce straordinarie performance in tutte le condizioni operative che richiedono eccellente trazione abbinata a carichi elevati. TR 144 è anche disponibile in versione "special", molto idonea per le operazioni di servizio pesante.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattorino

Version	STANDARD
Type	TT
Tyre Size	9.5 - 16
LI/SS	102 A6

Dimensions International Standard

Ply Rating	8
Section Width (mm)	245
Overall Diameter (mm)	850
Static Loaded Radius (mm)	388
Rolling Circumference (mm)	2558
Rim Rec	W 8 L
Rim Alt	8 LB
ECE	E11-106R-004327
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.80
30	850

Printed on 25/04/2024 16:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..