

TR 145 - Specifiche tecniche



Description

TR 145 è stato particolarmente sviluppato per trattori piccoli. Il particolare disegno del battistrada offre eccellente trazione e straordinarie proprietà di autopulitura. Il disegno largo e profondo dei ramponi assicura una vita prolungata dello pneumatico. TR 145 mostra un'ampia area di contatto che fornisce eccellente comfort di guida nonché elevata stabilità direzionale.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattorino

Version	STANDARD
Type	TT
Tyre Size	160/90 - 12
LI/SS	76 A6

Dimensions International Standard

Ply Rating	6
Section Width (mm)	160
Overall Diameter (mm)	631
Static Loaded Radius (mm)	294
Rolling Circumference (mm)	1969
Rim Rec	4.00
ECE	E11-106R-005854
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.50
30	400

Printed on 26/04/2024 05:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..