

TR 171 - Specifiche tecniche



Description

TR 171 è uno pneumatico con battistrada profondo idoneo per trattori nelle lavorazioni della terra. Grazie alle straordinarie proprietà di autopulitura, lo pneumatico è ideale per terreni umidi e bagnati. Realizzato con una miscela speciale, TR 171 garantisce eccellente trazione e durabilità anche nelle condizioni operative più dure.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	18.4 - 38
LI/SS	145 A8

Dimensions US Standard

Usa code	94040360
Ply Rating	10
Section Width (inch)	18.5
Overall Diameter (inch)	69.3
Static Loaded Radius (inch)	32.1
Rolling Circumference (inch)	211.2
Rim Rec	W 16 L
Rim Alt	W 15 L
ECE	E11-106R-003387
TRA Code	R1W+

Load capacity (lbs)

mph / psi	26
25	6400

Printed on 22/02/2024 04:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..