

TR 171 - Specifiche tecniche



Description

TR 171 è uno pneumatico con battistrada profondo idoneo per trattori nelle lavorazioni della terra. Grazie alle straordinarie proprietà di autopulitura, lo pneumatico è ideale per terreni umidi e bagnati. Realizzato con una miscela speciale, TR 171 garantisce eccellente trazione e durabilità anche nelle condizioni operative più dure.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	HD
Type	TT
Tyre Size	8.3 - 20
LI/SS	98 A8

Dimensions US Standard

Usa code	94062508
Ply Rating	8
Section Width (inch)	8.3
Overall Diameter (inch)	35.4
Static Loaded Radius (inch)	16.7
Rolling Circumference (inch)	109.6
Rim Rec	W 7
Rim Alt	W 6
ECE	E11-106R-007208
TRA Code	R1W+

Load capacity (lbs)

mph / psi	46
25	1650

Printed on 03/03/2024 16:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..