

## TR 171 - Specifiche tecniche



### Description

TR 171 è uno pneumatico con battistrada profondo idoneo per trattori nelle lavorazioni della terra. Grazie alle straordinarie proprietà di autopulitura, lo pneumatico è ideale per terreni umidi e bagnati. Realizzato con una miscela speciale, TR 171 garantisce eccellente trazione e durabilità anche nelle condizioni operative più dure.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	9.5 - 24
LI/SS	106 A6

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	240
Overall Diameter (mm)	1066
Static Loaded Radius (mm)	500
Rolling Circumference (mm)	3260
Rim Rec	W 8
Rim Alt	W 7
ECE	E4-106R-002031
TRA Code	R1W+

## Load capacity (Kg)

km/h / bar	2.10
30	950

Printed on 26/04/2024 18:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..