

TR 270 - Specifiche tecniche



Description

TR 270 è uno pneumatico per trattori idoneo per applicazioni di lavorazione della terra. Lo pneumatico è stato specialmente progettato per offrire massime prestazioni su terreni umidi e bagnati. In queste condizioni del suolo, ad uno pneumatico è richiesto di offrire grip superiore insieme a proprietà avanzate di autopulitura. TR 270 soddisfa perfettamente queste caratteristiche.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	23.1 - 34
LI/SS	160 A6

Dimensions International Standard

Ply Rating	14
Section Width (mm)	590
Overall Diameter (mm)	1850
Static Loaded Radius (mm)	841
Rolling Circumference (mm)	5532
Rim Rec	DW 20 A ; DW 20 B
ECE	E11-106R-004510
TRA Code	R2

Load capacity (Kg)

km/h / bar	2.20
30	4500

Printed on 19/04/2024 21:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..