

TR 273 - Specifiche tecniche



Description

TR 273 è uno pneumatico per trattori idoneo per le applicazioni di lavorazione della terra. Lo pneumatico è stato specialmente progettato per offrire massime prestazioni su terreni umidi e bagnati. In queste condizioni del suolo, ad uno pneumatico è richiesto di offrire grip superiore insieme a proprietà avanzate di autopulitura. TR 273 soddisfa perfettamente queste caratteristiche.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Trattore

Version	STANDARD
Type	TT
Tyre Size	14.9 - 28
LI/SS	126 A8

Dimensions US Standard

Usa code	94054121
Ply Rating	8
Section Width (inch)	15.2
Overall Diameter (inch)	55.5
Static Loaded Radius (inch)	25.6
Rolling Circumference (inch)	172
Rim Rec	W 13
Rim Alt	W 12
ECE	E11-106R-004516
TRA Code	R2

Load capacity (lbs)

mph / psi	26
25	3740

Printed on 17/04/2024 05:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..