

TR 317 - Specifiche tecniche

Description

TR 317 è idoneo per operazioni in ambito municipalità e le lavorazioni della terra con attrezzi agricoli e scavafossi. Lo pneumatico TR 317 mostra un'ampia area di contatto che fornisce eccellente grip e straordinaria stabilità in qualsiasi condizione oltre a eccellenti qualità di autopulitura.

UM

US Standard

Construction

BIAS

Machinery

Agricoltura: Attrezzi agricoli • Macchina per il raccolto di frutteti • Scavafossi



Version	HD
Type	TL
Tyre Size	18 X 8.50 - 8

Dimensions US Standard

Usa code	94045884
Ply Rating	6
Section Width (inch)	8.5
Overall Diameter (inch)	17.7
Static Loaded Radius (inch)	7.8
Rolling Circumference (inch)	51.4
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90

Load capacity (lbs)

mph / psi	34
10	1050

Printed on 05/12/2023 23:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..