

TR 319 - Specifiche tecniche



Description

TR 319 è uno pneumatico per attrezzi agricoli, macchine per il raccolto di frutteti e scavafossi nelle applicazioni in ambito municipalità nonché per la lavorazione della terra. Lo pneumatico mostra un'ampia area di contatto che si traduce in ottima trazione. Pertanto, TR 319 è molto idoneo per applicazioni su superficie bagnate che richiedono eccellenti doti di stabilità e autopulitura.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Macchina per il raccolto di frutteti • Scavafossi

Version	STANDARD
Type	TL
Tyre Size	29 X 12.50 - 15
LI/SS	106 B

Dimensions International Standard

Ply Rating	8
Section Width (mm)	312
Overall Diameter (mm)	755
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2264
Rim Rec	10 LB
ECE	E11-106R-004605

Load capacity (Kg)

km/h / bar	3.10
50	950

Printed on 22/04/2024 18:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..