

TR 390 - Specifiche tecniche



Description

TR 390 è uno pneumatico agro-industriale, idoneo per rimorchi per la canna dello zucchero e compattatori. Lo pneumatico TR 390 si distingue per l'elevata capacità di carico e l'aumentata durabilità. La sua versione "dual bead HD", a doppio tallone HD, è particolarmente idonea per i trattori industriali e le operazioni di trasporto con rimorchi, mentre la versione "dual bead HD special", a doppio tallone HD speciale, è ideale per operazioni di servizio pesante.

UM

International Standard

Construction

✚ BIAS

Machinery

Agricoltura: Rimorchio

Industriale: Compattatore

Version	STANDARD
Type	TL
Tyre Size	23.1 - 26
LI/SS	159 A6

Dimensions International Standard

Ply Rating	16
Section Width (mm)	595
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	690
Rolling Circumference (mm)	4545
SRI (mm)	750
Rim Rec	DW 20 B
ECE	E11-106R-004606
TRA Code	R3

Load capacity (Kg)

km/h / bar	2.30
30	4375

Printed on 26/04/2024 15:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..