

TR 390 - Specifiche tecniche



Description

TR 390 è uno pneumatico agro-industriale, idoneo per rimorchi per la canna dello zucchero e compattatori. Lo pneumatico TR 390 si distingue per l'elevata capacità di carico e l'aumentata durabilità. La sua versione "dual bead HD", a doppio tallone HD, è particolarmente idonea per i trattori industriali e le operazioni di trasporto con rimorchi, mentre la versione "dual bead HD special", a doppio tallone HD speciale, è ideale per operazioni di servizio pesante.

UM

International Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

Industriale: Compattatore

| | |
|-----------|----------------------|
| Version | HD DUAL BEAD SPECIAL |
| Type | TL |
| Tyre Size | 23.1 - 26 |
| LI/SS | 161 A6 |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Ply Rating | 18 |
| Section Width (mm) | 595 |
| Overall Diameter (mm) | 1560 |
| Static Loaded Radius (mm) | 690 |
| Rolling Circumference (mm) | 4545 |
| SRI (mm) | 750 |
| Rim Rec | DW 20 B |
| ECE | E11-106R-004629 |
| TRA Code | R3 |

Load capacity (Kg)

| km/h / bar | 2.60 |
|------------|------|
| 30 | 4625 |

Printed on 26/04/2024 18:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..