

## TR 390 - Specifiche tecniche



### Description

TR 390 è uno pneumatico agro-industriale, idoneo per rimorchi per la canna dello zucchero e compattatori. Lo pneumatico TR 390 si distingue per l'elevata capacità di carico e l'aumentata durabilità. La sua versione "dual bead HD", a doppio tallone HD, è particolarmente idonea per i trattori industriali e le operazioni di trasporto con rimorchi, mentre la versione "dual bead HD special", a doppio tallone HD speciale, è ideale per operazioni di servizio pesante.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Agricoltura: Rimorchio

Industriale: Compattatore

Version	HD DUAL BEAD SPECIAL
Type	TL
Tyre Size	23.1 - 26
LI/SS	157 A8

## Dimensions US Standard

Usa code	94030958
Ply Rating	18
Section Width (inch)	23.4
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 20 B
ECE	E11-106R-004629
TRA Code	R3

## Load capacity (lbs)

mph / psi	38
25	9090

Printed on 26/04/2024 23:40

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..