

TR 391 - Scheda tecnica



Description

TR 391 è uno pneumatico agro-industriale, idoneo per le operazioni di trasporto e di compattazione con rimorchi per la canna da zucchero e compattatori. TR 391 si distingue per l'elevata capacità di carico e un ciclo di vita prolungato.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Rimorchio

Industriale: Compattatore

SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
14.9 - 24	STANDARD	94005260	R3	119 A8	6	DW 13	DW 11 ; DW 13 L ; DW 12	15.9	50	22.6	149.8	TL	
14.9 - 24	STANDARD	94005277	R3	124 A8	8	DW 13	DW 11 ; DW 12 ; DW 13 L	15.9	50	22.6	149.8	TL	E11-106R-003365

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 08:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..