

## TR 393 (B) - Specifiche tecniche



### Description

TR 393 (B) è stato appositamente progettato per seminatrici, spargitori e macchine agricole su strada e fuori strada. Il design speciale del battistrada garantisce le migliori proprietà di galleggiamento e autopulitura, oltre a una lunga durata. Grazie all'ampia superficie di contatto, il TR 393 (B) assicura un'eccellente trazione e riduce al minimo il compattamento del terreno.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli • Spargitore

Version	STUBBLE RESISTANT
Type	TL
Tyre Size	31 X 13.50 - 15
LI/SS	124 B

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	350
Overall Diameter (mm)	777
Rim Rec	10 LB
ECE	E11-106R-008131
TRA Code	R3

## Load capacity (Kg)

km/h / bar	5.20
50	1600

Printed on 02/05/2024 22:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..