

## TR 393 - Specifiche tecniche



### Description

TR 393 è stato specialmente sviluppato per presse per balle di fieno, spargitori e attrezzi agricoli su strada e fuori strada. Il particolare disegno del battistrada assicura ottime proprietà di galleggiamento e autopulitura nonché una lunga vita operativa. Grazie alla larga area di contatto, TR 393 offre eccellente trazione e minimizza la compattazione del suolo.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli • Spargitore

Version	STANDARD
Type	TL
Tyre Size	16.5L - 16.1 SL
LI/SS	128 B

## Dimensions International Standard

Ply Rating	6
Section Width (mm)	420
Overall Diameter (mm)	1025
Static Loaded Radius (mm)	461
Rolling Circumference (mm)	2966
Rim Rec	W14C
Rim Alt	W14CH
TRA Code	I2

## Load capacity (Kg)

km/h / bar	1.70
50	1800

Printed on 23/04/2024 20:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..