

## TR 393 - Scheda tecnica



### Description

TR 393 è stato specialmente sviluppato per presse per balle di fieno, spargitori e attrezzi agricoli su strada e fuori strada. Il particolare disegno del battistrada assicura ottime proprietà di galleggiamento e autopulitura nonché una lunga vita operativa. Grazie alla larga area di contatto, TR 393 offre eccellente trazione e minimizza la compattazione del suolo.

### UM

International Standard

### Construction

❖ BIAS

### Machinery

Agricoltura: Pressa per balle di fieno • Attrezzi agricoli • Spargitore

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
16.5L - 16.1 SL	STANDARD	I2	128 B	6	W14C	W14CH	420	1025	461	2966	TL	E11-106R-007109
21.5L - 16.1 SL	STANDARD	I2	146 B	10	W 18 CH	W 16 CH	546	1154			TL	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 22:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..