

## TR 461 - Specifiche tecniche



### Description

TR 461 è uno pneumatico BKT sviluppato per le applicazioni municipalità e manutenzione con trattori nonché per le operazioni di carico con sollevatori telescopici. La protezione del fianco è caratterizzata dalla particolare resistenza a tagli e lacerazioni che garantisce una vita più lunga dello pneumatico anche su superfici dure insieme ad eccellente stabilità.

### UM

US Standard

### Construction

 BIAS

### Machinery

Industriale: Terna • Sollevatore telescopico • Trattore industriale

Version	STANDARD
Type	TL
Tyre Size	21L - 24
LI/SS	157 A8

## Dimensions US Standard

Usa code	94016785
Ply Rating	14
Section Width (inch)	21.3
Overall Diameter (inch)	54.5
Static Loaded Radius (inch)	23.9
Rolling Circumference (inch)	160.3
Rim Rec	DW 18 L
TRA Code	R4

## Load capacity (lbs)

mph / psi	36
25	9090

Printed on 23/04/2024 17:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..