

TR 678 - Specifiche tecniche



Description

TR 678 è stato particolarmente sviluppato per applicazioni forestali. Il robusto disegno dei tasselli garantisce trazione e autopulitura eccellenti. La tenace struttura della carcassa si traduce in elevata capacità di carico, mentre le cinture in acciaio proteggono lo pneumatico da forature e danni. TR 678 è caratterizzato da una mescola resistente ai tagli che garantisce, anche su terreni difficili in condizioni estreme, eccellente resistenza a tagli e lacerazioni.

UM

US Standard

Construction

 BIAS

Machinery

Agricoltura: Attrezzi agricoli • Rimorchio
Industriale: Escavatore • Rimorchio

Version	STEEL BELTED
Type	TL
Tyre Size	710/55 - 34
LI/SS	173 A2/ 168 A6

Dimensions US Standard

Usa code	94069026
Ply Rating	20
Section Width (inch)	27.6
Overall Diameter (inch)	64.6
Static Loaded Radius (inch)	29.8
Rolling Circumference (inch)	192.5
Rim Rec	DW 24 B
TRA Code	LS2

Load capacity (lbs)

mph / psi	46
20	12350
5	14330

Printed on 20/04/2024 00:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..