

TRAC GRADER + - Specifiche tecniche



Description

TRAC GRADER + (G-2) è uno pneumatico a tele incrociate per motolivellatrici, che rappresenta una scelta eccellente per i clienti orientati al budget. La carcassa durevole è progettata per resistere nel tempo. Il disegno autopulente del battistrada mostra una proporzione rampone-spazio che fornisce la migliore trazione in tutte le condizioni. La versione special è realizzata con una miscela speciale, resistente a tagli e strappi.

UM

US Standard

Construction

✦ BIAS

Machinery

OTR: Motolivellatrice

Version	STANDARD
Type	TL
Tyre Size	13.00 - 24

Dimensions US Standard

Usa code	94014569
Ply Rating	14
Overall Width (inch)	13.4
Overall Diameter (inch)	50.4
Static Loaded Radius (inch)	23.6
Rolling Circumference (inch)	155.2
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC
ECE	E11-106R-003630
TRA Code	G2

Load capacity (lbs)

mph / psi	51
25	6600

Printed on 21/04/2024 00:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..