

TRAC GRADER + - Specifiche tecniche



Description

TRAC GRADER + (G-2) è uno pneumatico a tele incrociate per motolivellatrici, che rappresenta una scelta eccellente per i clienti orientati al budget. La carcassa durevole è progettata per resistere nel tempo. Il disegno autopulente del battistrada mostra una proporzione rampone-spazio che fornisce la migliore trazione in tutte le condizioni. La versione special è realizzata con una miscela speciale, resistente a tagli e strappi.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Motolivellatrice

| | |
|-----------|------------|
| Version | SPECIAL |
| Type | TL |
| Tyre Size | 14.00 - 24 |

Dimensions US Standard

| | |
|------------------------------|--|
| Usa code | 94014699 |
| Ply Rating | 12 |
| Overall Width (inch) | 14.3 |
| Overall Diameter (inch) | 53.1 |
| Static Loaded Radius (inch) | 23.5 |
| Rolling Circumference (inch) | 157.1 |
| Rim Rec | 8.00 TG SDC |
| Rim Alt | 9.00/1.5 (DC) ; 10.00/VA SDC; 10.00 WA SDC |
| TRA Code | G2 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 36 |
| 25 | 6800 |

Printed on 20/04/2024 08:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..