

## V-FLEXA - Specifiche tecniche



### Description

V-FLEXA è un pneumatico radiale appositamente progettato per rimorchi agricoli. È un prodotto flotation di ultima generazione dotato della tecnologia VF, che consente il trasporto di carichi pesanti sia su campo che su strada con una pressione di gonfiaggio inferiore del 30% rispetto a quella di un pneumatico standard delle stesse dimensioni. Ulteriori cinture in acciaio conferiscono maggiore resistenza alla carcassa contro aggressioni. V-FLEXA non solo supporta carichi pesanti in totale sicurezza, ma evita anche la compattazione del suolo grazie alla perfetta distribuzione del peso. Inoltre, V-FLEXA offre ottime proprietà di autopulitura, durabilità e bassa resistenza al rotolamento.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricoltura: Rimorchio

Version	STEEL BELTED
Type	TL
Tyre Size	VF 600/55 R 26.5
LI/SS	167 D

## Dimensions US Standard

Usa code	94063949
Section Width (inch)	24.2
Overall Diameter (inch)	52.8
Static Loaded Radius (inch)	22.8
Rolling Circumference (inch)	156.9
Rim Rec	AG20.00
ECE	E11-106R-006017

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41
45	4700	6010	7310	8300	9620	10930
40	5160	6610	8050	9130	10580	12020
30	6050	7730	9420	10690	12370	14060
25	6660	5830	10390	11780	13640	15500
5	8470	10830	13200	14970	17330	19700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/12/2024 08:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..