

V-FLEXA - Specifiche tecniche



Description

V-FLEXA è un pneumatico radiale appositamente progettato per rimorchi agricoli. È un prodotto flotation di ultima generazione dotato della tecnologia VF, che consente il trasporto di carichi pesanti sia su campo che su strada con una pressione di gonfiaggio inferiore del 30% rispetto a quella di un pneumatico standard delle stesse dimensioni. Ulteriori cinture in acciaio conferiscono maggiore resistenza alla carcassa contro aggressioni. V-FLEXA non solo supporta carichi pesanti in totale sicurezza, ma evita anche la compattazione del suolo grazie alla perfetta distribuzione del peso. Inoltre, V-FLEXA offre ottime proprietà di autopulitura, durabilità e bassa resistenza al rotolamento.

UM

US Standard

Construction

 RADIAL

Machinery

Agricoltura: Rimorchio

| | |
|--------------------|------------------|
| Version | STEEL BELTED |
| Type | TL |
| Tyre Size | VF 710/50 R 26.5 |
| LI/SS | 176 D |
| LI/SS DRIVE WHEEL | 176 D |
| LI/SS FREE ROLLING | 176 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94074839 |
| Section Width (inch) | 28.6 |
| Overall Diameter (inch) | 54.4 |
| Static Loaded Radius (inch) | 23.6 |
| Rolling Circumference (inch) | 165.1 |
| Rim Rec | AG 24.00 |
| ECE | E11-106R-008833 |

Load capacity (lbs)

| mph / psi | 12 | 17 | 23 | 29 | 35 | 41 | 46 |
|-----------|-------|-------|-------|-------|-------|-------|-------|
| 45 | 5710 | 7280 | 8560 | 9990 | 11270 | 12840 | 14260 |
| 40 | 6270 | 8000 | 9400 | 10960 | 12370 | 14090 | 15660 |
| 30 | 7330 | 9350 | 11010 | 12840 | 14480 | 16490 | 18320 |
| 25 | 8080 | 10310 | 12130 | 14150 | 15970 | 18180 | 20200 |
| 5 | 10280 | 13100 | 15410 | 17980 | 20290 | 23120 | 25680 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 07/12/2024 03:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..