

## XL GRIP (BHL) - Scheda tecnica



### Description

XL GRIP (BHL) è stato particolarmente sviluppato per terne che vengono impiegate in operazioni pesanti nelle applicazioni di scavo, spianamento e carico. Il disegno non direzionale del battistrada assicura ottima trazione e stabilità. La speciale mescola del battistrada si traduce in eccellente resistenza a tagli e lacerazioni e prolunga la vita del battistrada.

### UM

US Standard

### Construction

❖ BIAS

### Machinery

Industriale: Terna

| SIZE         | Version               | USACode  | LI/SS  | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT                | OW   | OD   | SLR  | RC    | Type |
|--------------|-----------------------|----------|--------|--------------------|----|---------|------------------------|------|------|------|-------|------|
| 9.00 - 16    | STANDARD              | 94051106 | 137 A6 |                    | 16 | 6.50 H  | 6.00 G                 | 10.2 | 35.8 | 0    | 0     | TT   |
| 9.00 - 16    | STANDARD              | 94051267 | 132 A6 |                    | 12 | 6.50 H  | 6.00 G                 | 10.2 | 35.8 | 0    | 0     | TT   |
| 12.5/80 - 18 | STANDARD              | 94050307 |        | 142 A8             | 12 | W 9     | 11                     | 12   | 38.6 | 0    | 0     | TT   |
| 12.5/80 - 18 | STANDARD              | 94050376 |        | 142 A8             | 12 | W 9     | 11                     | 12   | 38.6 | 0    | 0     | TL   |
| 12.5/80 - 18 | STANDARD              | 94051533 |        | 148 A8             | 16 | W 9     | 11                     | 12   | 38.6 | 0    | 0     | TT   |
| 10.00 - 20   | ARAMID + STEEL BELTED | 94050727 |        |                    | 18 | 7.5     | 7.0                    | 11.2 | 42.3 | 19.9 | 128.2 | TT   |
| 10.00 - 20   | ARAMID BELTED         | 94048915 |        |                    | 18 | 7.5     | 7.0                    | 11.2 | 42.3 | 19.9 | 128.2 | TT   |
| 10.00 - 20   | INDUSTRIAL            | 94047932 |        |                    | 18 | 7.5     | 7.0                    | 11.2 | 42.3 | 19.9 | 128.2 | TT   |
| 10.00 - 20   | STEEL BELTED          | 94048908 |        |                    | 18 | 7.5     | 7.0                    | 11.2 | 42.3 | 19.9 | 128.2 | TT   |
| 12.00 - 20   | INDUSTRIAL            | 94059218 |        |                    | 20 | 8.5     | 8.0                    | 12.6 | 45.5 | 21.5 | 136.4 | TT   |
| 12.00 - 24   | INDUSTRIAL            | 94046270 |        |                    | 20 | 8.5     | 8.0                    | 12.6 | 49.2 | 23   | 146.1 | TT   |
| 14.9 - 24    | INDUSTRIAL            | 94045396 | 145 A8 |                    | 12 | DW 13   | DW 11 ; DW 12 ; DW 13L | 15   | 48.8 | 22.6 | 143.5 | TT   |
| 16.9 - 28    | INDUSTRIAL            | 94043873 | 152 A8 |                    | 12 | DW 15L  | DW 14L                 | 17.7 | 55.1 | 25.2 | 164.4 | TT   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 11/05/2025 16:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..