XL GRIP (E3) - Specifiche tecniche

Description

XL GRIP (E-3) è uno pneumatico a tele incrociate per dumper rigidi, progettato appositamente per minimizzare il rischio di tagli e perforazioni in condizioni che richiedono eccezionale trazione. Queste caratteristiche si traducono in una vita prolungata dello pneumatico.

UM

US Standard

Construction

BIAS

Machinery

OTR: Dumper rigido

Version	STANDARD
Type	TL
Tyre Size	18.00 - 25

Dimensions US Standard

Usa code	94015788
Ply Rating	40
Overall Width (inch)	20.1
Overall Diameter (inch)	63.6
Static Loaded Radius (inch)	29.1
Rolling Circumference (inch)	188.2
Rim Rec	13.00/2.5
Rim Alt	15.00/2.5
TRA Code	E3/L3

Load capacity (lbs)

mph / psi	102	138
30	21500	-
5	-	37500

Printed on 28/04/2024 00:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..