

XL GRIP IND3 (RTG) - Specifiche tecniche



Description

XL GRIP (IND-3) è un pneumatico a tele incrociate per gru RTG nelle applicazioni di impilatura e sollevamento. Lo pneumatico è caratterizzato da una carcassa robusta realizzata con una miscela appositamente formulata che assicura un ciclo di vita prolungato del prodotto.

UM

US Standard

Construction

 BIAS

Machinery

Industriale: Gru RTG

| | |
|-----------|------------|
| Version | INDUSTRIAL |
| Type | TL |
| Tyre Size | 21.00 - 25 |

Dimensions US Standard

| | |
|------------------------------|-----------|
| Usa code | 94063840 |
| Ply Rating | 44 |
| Overall Width (inch) | 22.7 |
| Overall Diameter (inch) | 68.9 |
| Static Loaded Radius (inch) | 31.1 |
| Rolling Circumference (inch) | 204.1 |
| Rim Rec | 15.00/3.0 |
| Rim Alt | 17.00/3.0 |
| TRA Code | IND3 |

Load capacity (lbs)

| mph / psi | 145 |
|-----------|-------|
| 5 | 64300 |

Printed on 19/04/2024 23:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..