

XL GRIP (T) - Specifiche tecniche



Description

XL GRIP (E-3) è molto idoneo per autocarri con cassone ribaltabile che trasportano carichi pesanti nelle applicazioni di miniera. La miscela del battistrada è sviluppata per minimizzare il rischio di tagli e perforazioni sui terreni più ardui. XL GRIP (E-3) offre eccezionale trazione, assicurando un ciclo di vita prolungato dello pneumatico.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Carro con cassone ribaltabile

Version	STANDARD
Type	TT
Tyre Size	8.25 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	238
Overall Diameter (mm)	870
Rim Rec	6.50 H
Rim Alt	6.00 G
Tread Depth	20

Load capacity (Kg)

km/h / bar	8.20
50 LS	2070
50 LD	1960

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 29/04/2025 06:57

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..