

XL GRIP ULTRA - Specifiche tecniche



Description

XL GRIP ULTRA è uno pneumatico a tele incrociate progettato per dumper impiegati in operazioni di servizio pesante come nelle applicazioni minerarie, nelle cave o ai cantieri. Il disegno non direzionale del battistrada offre eccellente trazione anteriore e laterale. Lo pneumatico è caratterizzato da una robusta carcassa in nylon con giunti di collegamento ottimizzati nonché da una special miscela del battistrada per assicurare elevata resistenza a tagli e forature, eccellente durabilità e resistenza all'usura insieme a ottime proprietà di autopulitura anche su superfici rocciose.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Carro con cassone ribaltabile

Version	STANDARD
Type	TT
Tyre Size	11.00 - 20

Dimensions US Standard

Usa code	94064212
Ply Rating	18
Overall Width (inch)	11.7
Overall Diameter (inch)	43.9
Static Loaded Radius (inch)	20.8
Rolling Circumference (inch)	132.6
Rim Rec	8.0
Rim Alt	7.5

Load capacity (lbs)

mph / psi	110
55 LS/LD	6610

Printed on 07/05/2024 01:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..