

## AGRI GRIP - Especificações técnicas



### Description

AGRI GRIP é um pneu utilizado nas operações de transporte, sendo especialmente apropriado para aplicações com reboques para canas-de-açúcar. AGRI GRIP é dotado de uma carcaça robusta que proporciona uma capacidade de carga elevada, junto com uma resistência excelente aos cortes e lacerações. O desenho especial do piso do pneu assegura uma vida de serviço prolongada.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agricultura: Reboque

Version	DUAL BEAD
Type	TL
Tyre Size	23.1 - 26

## Dimensions International Standard

Ply Rating	18
Overall Width (mm)	595
Overall Diameter (mm)	1560
Static Loaded Radius (mm)	708
Rolling Circumference (mm)	4658
Rim Rec	DW 20 B

## Load capacity (Kg)

km/h / bar	2.60
30 FR LLV	5600

Printed on 20/04/2024 07:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..