

AGRI TRAILER - Especificações técnicas



Description

AGRI TRAILER foi especificadamente desenvolvido para reboques do trator. O pneu é o ideal para a agricultura moderna, sendo apropriado para aplicações de transporte tanto na estrada como fora da estrada. Aa sua construção robusta traduz-se nune elevada capacidade de carga, enquanto o piso do pneu, extra-profundo, permite uma melhor quilometragem e uma vida operacional mais larga.

UM

International Standard

Construction

 BIAS

Machinery

Agricultura: Reboque

Version	STANDARD
Type	TT
Tyre Size	10.00 - 20

Dimensions International Standard

Ply Rating	18
Section Width (mm)	286
Overall Diameter (mm)	1080
Rim Rec	7.5
Rim Alt	7.0 ; 8.0

Load capacity (Kg)

km/h / bar	9.30	8.60
30 LS	3845	-
30 LD	-	3405

Printed on 25/04/2024 15:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..