

AGRIMAX ELOS - Dados técnicos



Description

AGRIMAX ELOS foi projetado para exprimir a máxima tração, mesmo em condições de utilização especialmente problemáticas em terrenos molhados - por exemplo arrozais - e pantanosos. O desenho do piso do pneu foi estudado especificadamente para garantir ótimas qualidades de auto limpeza, essencial nos trabalhos em campos lamacentos e durante as deslocções. Para otimizar a produtividade da empresa agrícola, no **design** do pneu Agrimax Elos foram integrados cordões de proteção nos flancos para assegurar em qualquer momento a máxima proteção de possíveis prejuízos.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Trator

| SIZE | Version | TRA Code | LI/SS | RIM REC | RIM ALT | SW | OD | SLR | RC | SRI | Type | ECE |
|-----------------------------------|----------|----------|--------------|---------|--|-----|------|-----|------|-----|------|-----------------|
| 420/85 R 28 (16.9 R 28) | STANDARD | R2 | 139 A8/B | W 15 L | W 13 ; W 14 L | 438 | 1467 | 665 | 4349 | 700 | TL | E4-106R-000768 |
| 480/70 R 34 | STANDARD | R2 | 155 A8/155 B | W 15 L | W 16 L ; W 14 L | 500 | 1605 | 733 | 4868 | 750 | TL | E11-106R-007532 |
| 340/85 R 38 (13.6 R 38) | STANDARD | R2 | 133 A8/B | W 12 | W 11 | 353 | 1602 | 735 | 4774 | 775 | TL | E4-106R-001477 |
| 380/85 R 38 (14.9 R 38) | STANDARD | R2 | 139 A8/B | W 12 | W 11 ; W 13 | 380 | 1662 | 772 | 4994 | 775 | TL | E4-106R-000779 |
| 420/85 R 38 (16.9 R 38) | STANDARD | R2 | 144 A8/B | W 15 L | W 13 ; W 14 L | 438 | 1735 | 785 | 5135 | 825 | TL | E4-106R-000780 |
| 480/80 R 38 (18.4 R 38) | STANDARD | R2 | 149 A8/B | W 16 L | W 15 L ; DW 16 L | 489 | 1803 | 821 | 5356 | 825 | TL | E11-106R-002991 |
| 710/70 R 38 | STANDARD | R2 | 178 A8/B | DW 23 B | DW 25 B | 716 | 2019 | 915 | 6103 | 925 | TL | E11-106R-004896 |
| 480/80 R 42 (18.4 R 42) | STANDARD | R2 | 151 A8/B | DW 16 L | DD 16 L ; W 16 L | 489 | 1890 | 857 | 5629 | 875 | TL | E4-106R-001481 |
| 520/85 R 42 (20.8 R 42) | STANDARD | R2 | 157 A8/B | DW 16 L | DD 18 L ; DW 18 L | 516 | 1988 | 904 | 5865 | 925 | TL | E4-106R-000793 |
| 520/85 R 46 | STANDARD | R2 | 169 A8/169 B | DW 16 L | DW 15 L ; DW 18 L ; W 15 L ; W 16 L ; W 18 L ; DD 16 L ; DD 18 L | 530 | 2075 | 957 | 6293 | 975 | TL | E11-106R-007935 |

Printed on 10/12/2023 11:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..