

AGRIMAX FORCE - Especificações técnicas



Description

AGRIMAX FORCE, o produto de ponta da BKT, é um pneu radial devidamente projetado para aplicações de tratamento do terreno, de transporte e de colheita com tratores de elevada potência, garantindo máximas prestações e eficiência. Com a tecnologia IF, este pneu permite-lhe transportar cargas pesadas a pressões de enchimento inferiores em comparação com o pneu estandarte reduzindo a compactação do solo. AGRIMAX FORCE é dotado de talão reforçado e assegura uma tração maior, propriedades de autolimpeza e economia de combustível, bem como uma experiência de condução confortável.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Ceifeira • Trator de alta potencia

Version	STANDARD
Type	TL
Tyre Size	IF 600/70 R 28
LI/SS	164 D

Dimensions US Standard

Usa code	94044689
Section Width (inch)	23.7
Overall Diameter (inch)	61.1
Static Loaded Radius (inch)	27.3
Rolling Circumference (inch)	183.2
Rim Rec	DW 21 B
Rim Alt	DW 20 B
ECE	E4-106R-000795
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
45	4710	5410	6220	7020	7810	8620	9420	10030
from 40 to 25	5180	5950	6830	7720	8600	9480	10360	11000
20	5380	6180	7100	8020	8940	9850	10770	11460
12	5590	6430	7370	8330	9280	10230	11190	11900
5	6570	7550	8670	9800	10910	12040	13150	14000
*Upto 5 Cyc with front loader	7250	8330	9570	10800	12040	13270	14510	15430
5 HT	5380	6180	7100	8020	8940	9850	10770	11460

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Printed on 26/04/2024 08:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..