

## AGRIMAX RI 818 - Especificações técnicas



### Description

AGRIMAX RI 818 é um pneu radial projetado para aplicações de irrigação com pivôs centrais de irrigação. O especial desenho do piso do pneu fornece uma excelente tração em condições molhados e húmidos, bem como extraordinárias qualidades de autolimpagem.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pivô central de irrigação

Version	STANDARD
Type	TL
Tyre Size	320/85 R 38 (12.4 R 38)
LI/SS	154

## Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	1509
Static Loaded Radius (mm)	691
Rolling Circumference (mm)	4565
SRI (mm)	725
Rim Rec	W 10
Rim Alt	W 9 ; W 11

## Load capacity (Kg)

km/h / bar	1.6
CREEP	3750

\* - CREEP SPEED - 200 FT/30 MIN ( 61 M/30 MIN ) / For CREEP loads inflation pressure to be increased by +6 psi

Printed on 23/04/2024 23:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..