

## AGRIMAX RT 600 - Especificações técnicas

### Description

AGRIMAX RT 600 é o pneu apropriado para prados e aplicações para a colheita e o espalhamento. Graças à sua ampla área de contacto, AGRIMAX RT 600 garante uma distribuição de pressão otimizada no terreno reduzindo os danos nos prados e protegendo o solo. Graças à tecnologia com ombros arredondados e um número elevado de blocos, assegura ótima estabilidade e tração.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Ceifeira • Espalhador • Trator



Version	STANDARD
Type	TL
Tyre Size	750/70 R 26
LI/SS	172 A8/B

## Dimensions International Standard

Section Width (mm)	780
Overall Diameter (mm)	1750
Static Loaded Radius (mm)	785
Rolling Circumference (mm)	5269
SRI (mm)	825
Rim Rec	DW 25 B
Rim Alt	DW 24 B
ECE	E11-106R-007934

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
50	2710	3150	3595	4035	4475	4915	5420	5735	6300	-	-
40	2710	3150	3595	4035	4475	4915	5420	5735	6300	-	-
30	2905	3375	3850	4320	4795	5265	5805	6145	6750	-	-
10 LT	3635	4225	4820	5410	6000	6595	7270	7690	8450	-	-
10 HT	2905	3375	3850	4320	4795	5265	5805	6145	6750	-	-
10 Cyc	-	5065	5775	6480	7190	7900	8710	9215	10125	10285	10710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/10/2024 16:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..