

AGRIMAX RT 657 - Especificações técnicas



Description

AGRIMAX RT 657 é o pneu ideal para lavrar o terreno e para a utilização na estrada; algumas medidas também são apropriadas para a vindima. O pneu assegura um excelente conforto de condução, bem como as poupanças significativas de combustível. Apresenta uma capacidade de carga elevada mesmo em altas velocidades. AGRIMAX RT 657 é a escolha melhor para quem necessita de um pneu versátil e seguro sem comprometer as performances.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Trator • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	320/65 R 18
LI/SS	125 A8/B

Dimensions International Standard

Section Width (mm)	310
Overall Diameter (mm)	885
Static Loaded Radius (mm)	400
Rolling Circumference (mm)	2667
SRI (mm)	400
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-008145
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	1.8	2.0	2.8	3.2
50	545	645	745	825	925	1010	1205	1340	1505	1650
40	545	645	745	825	925	1010	1205	1340	1505	1650
30	585	695	800	885	995	1080	1295	1435	1615	1770
10 LT	735	865	1000	1110	1245	1355	1620	1795	2020	2215
10 HT	585	695	800	885	995	1080	1295	1435	1615	1770

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/03/2025 13:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..