

AGRIMAX RT 657 - Especificações técnicas



Description

AGRIMAX RT 657 é o pneu ideal para lavrar o terreno e para a utilização na estrada; algumas medidas também são apropriadas para a vindima. O pneu assegura um excelente conforto de condução, bem como as poupanças significativas de combustível. Apresenta uma capacidade de carga elevada mesmo em altas velocidades. AGRIMAX RT 657 é a escolha melhor para quem necessita de um pneu versátil e seguro sem comprometer as performances.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Trator • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	440/65 R 24
LI/SS	135 D/138 A8

Dimensions International Standard

Section Width (mm)	441
Overall Diameter (mm)	1182
Static Loaded Radius (mm)	538
Rolling Circumference (mm)	3546
SRI (mm)	575
Rim Rec	W 14 L
Rim Alt	W 13 ; W 15 L
ECE	E4-106R-000616
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1050	1225	1375	1530	1680	1810	2010	2180
50	1100	1285	1445	1605	1765	1905	2110	2290
40	1135	1325	1490	1655	1820	1960	2175	2360
30	1205	1410	1585	1760	1935	2085	2310	2510
10 LT	1405	1640	1845	2050	2255	2430	2695	2925
10 HT	1205	1410	1585	1760	1935	2085	2310	2510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/03/2025 12:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..