

## AGRIMAX RT 657 - Especificações técnicas



### Description

AGRIMAX RT 657 é o pneu ideal para lavrar o terreno e para a utilização na estrada; algumas medidas também são apropriadas para a vindima. O pneu assegura um excelente conforto de condução, bem como as poupanças significativas de combustível. Apresenta uma capacidade de carga elevada mesmo em altas velocidades. AGRIMAX RT 657 é a escolha melhor para quem necessita de um pneu versátil e seguro sem comprometer as performances.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Trator • Vindimadora

|           |              |
|-----------|--------------|
| Version   | SPECIAL      |
| Type      | TL           |
| Tyre Size | 540/65 R 30  |
| LI/SS     | 150 D/153 A8 |

## Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 530            |
| Overall Diameter (mm)      | 1464           |
| Static Loaded Radius (mm)  | 670            |
| Rolling Circumference (mm) | 4403           |
| SRI (mm)                   | 700            |
| Rim Rec                    | W 16 L         |
| Rim Alt                    | W 18 L         |
| ECE                        | E4-106R-000651 |
| TRA Code                   | R1W            |

## Load capacity (Kg)

| km/h / bar | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 1610 | 1880 | 2115 | 2345 | 2580 | 2785 | 3085 | 3350 |
| 50         | 1690 | 1975 | 2220 | 2465 | 2715 | 2925 | 3240 | 3520 |
| 40         | 1755 | 2045 | 2300 | 2555 | 2815 | 3030 | 3360 | 3650 |
| 30         | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |
| 10 LT      | 2160 | 2515 | 2830 | 3145 | 3460 | 3730 | 4135 | 4490 |
| 10 HT      | 1855 | 2160 | 2430 | 2700 | 2970 | 3200 | 3550 | 3855 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 17/03/2025 12:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..