

## AGRIMAX RT 657 - Especificações técnicas



### Description

AGRIMAX RT 657 é o pneu ideal para lavrar o terreno e para a utilização na estrada; algumas medidas também são apropriadas para a vindima. O pneu assegura um excelente conforto de condução, bem como as poupanças significativas de combustível. Apresenta uma capacidade de carga elevada mesmo em altas velocidades. AGRIMAX RT 657 é a escolha melhor para quem necessita de um pneu versátil e seguro sem comprometer as performances.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Trator • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	600/65 R 28
LI/SS	154 D/157 A8

## Dimensions US Standard

Usa code	94032129
Section Width (inch)	24.1
Overall Diameter (inch)	58.7
Static Loaded Radius (inch)	26.4
Rolling Circumference (inch)	176
Rim Rec	DW 20 B
Rim Alt	W 18 L
ECE	E4-106R-000621
TRA Code	R1W

## Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	3970	4630	5210	5790	6370	6870	7610	8250
30	4180	4870	5480	6080	6690	7220	7990	8690
25	4360	5090	5730	6370	7010	7550	8370	9090
20	4570	5330	6000	6670	7330	7900	8750	9510
5 LT	5320	6210	6990	7760	8530	9200	10200	11080
5 HT	4570	5330	6000	6670	7330	7900	8750	9510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 16/03/2025 04:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..