

AGRIMAX RT 765 - Especificações técnicas



Description

AGRIMAX RT 765, um pneu da série 70 da BKT, é ideal para equipar os tratores mais modernos ocupados em aplicações pesadas, tais como laborações do terreno, deslocamentos no campo e em estrada, a vindima e pulverizações. A ampla área de contato garante a melhor tração e conforto em todas as superfícies em qualquer altura. Este pneu apresenta propriedades de autolimpeza excelentes e uma compactação do solo reduzida. Estão disponíveis dois tamanhos com tecnologia de cintos em aço.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Trator • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	480/70 R 34
LI/SS	155 D

Dimensions US Standard

Usa code	94063109
Section Width (inch)	18.9
Overall Diameter (inch)	62.2
Static Loaded Radius (inch)	28.7
Rolling Circumference (inch)	188.5
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005834
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	47
40	3340	3940	4530	5050	5640	6150	6760	7260	7950	8540
30	3510	4130	4760	5300	5930	6470	7100	7630	8360	8970
25	3660	4310	4960	5520	6180	6750	7400	7960	8710	9360
20	3840	4530	5210	5810	6490	7090	7770	8370	9150	9830
5 LT	4480	5270	6070	6770	7560	8260	9050	9740	10660	11450
5 HT	3840	4530	5210	5810	6490	7090	7770	8370	9150	9830

Printed on 26/04/2024 15:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..