

AGRIMAX RT 765 - Especificações técnicas



Description

AGRIMAX RT 765, um pneu da série 70 da BKT, é ideal para equipar os tratores mais modernos ocupados em aplicações pesadas, tais como laborações do terreno, deslocamentos no campo e em estrada, a vindima e pulverizações. A ampla área de contato garante a melhor tração e conforto em todas as superfícies em qualquer altura. Este pneu apresenta propriedades de autolimpeza excelentes e uma compactação do solo reduzida. Estão disponíveis dois tamanhos com tecnologia de cintos em aço.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Trator • Vindimadora

| | |
|-----------|-------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 710/70 R 38 |
| LI/SS | 166 D |

Dimensions US Standard

| | |
|------------------------------|-----------------|
| Usa code | 94066773 |
| Section Width (inch) | 28.2 |
| Overall Diameter (inch) | 77.1 |
| Static Loaded Radius (inch) | 33.8 |
| Rolling Circumference (inch) | 226.4 |
| Rim Rec | DW 23 B |
| ECE | E11-106R-005837 |
| TRA Code | R1W |

Load capacity (lbs)

| mph / psi | 9 | 12 | 15 | 17 | 20 | 23 |
|-----------|------|-------|-------|-------|-------|-------|
| 40 | 6430 | 7480 | 8530 | 9590 | 10640 | 11680 |
| 30 | 6760 | 7860 | 8960 | 10060 | 11170 | 12270 |
| 25 | 7040 | 8200 | 9350 | 10500 | 11650 | 12800 |
| 20 | 7400 | 8610 | 9810 | 11020 | 12230 | 13440 |
| 5 LT | 8620 | 10030 | 11440 | 12850 | 14260 | 15660 |
| 5 HT | 7400 | 8610 | 9810 | 11020 | 12230 | 13440 |

Printed on 26/04/2024 23:19

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..