

AGRIMAX RT 945 - Especificações técnicas



Description

AGRIMAX RT 945 foi especialmente desenvolvido para culturas em linhas: não prejudica as culturas e protege a colheita. Além disso, as extraordinárias capacidades de autolimpeza permitem a mudança rápida das operações no campo para a utilização na estrada, onde AGRIMAX RT 945 demonstra performances brilhantes. A carcaça robusta assegura uma estabilidade excelente, máxima tração e durabilidade excepcional.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Trator

Version	STANDARD
Type	TL
Tyre Size	320/90 R 42 (12.4 R 42)
LI/SS	139 A8/B

Dimensions US Standard

Usa code	94038664
Section Width (inch)	12.6
Overall Diameter (inch)	64.7
Static Loaded Radius (inch)	29.9
Rolling Circumference (inch)	194.6
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E4-106R-000783
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	17	23	29	35	41
30	2900	3760	4610	4980	5360	-
25	2900	3760	4610	4980	5360	-
20	3110	4020	4950	5350	5740	-
5	4270	5220	6350	7400	7800	8040

Printed on 19/04/2024 16:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..