

AGRIMAX RT 945 - Especificações técnicas



Description

AGRIMAX RT 945 foi especialmente desenvolvido para culturas em linhas: não prejudica as culturas e protege a colheita. Além disso, as extraordinárias capacidades de autolimpeza permitem a mudança rápida das operações no campo para a utilização na estrada, onde AGRIMAX RT 945 demonstra performances brilhantes. A carcaça robusta assegura uma estabilidade excelente, máxima tração e durabilidade excepcional.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Trator

Version	STANDARD
Type	TL
Tyre Size	320/90 R 54 (12.4 R 54)
LI/SS	156 A8/B

Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	1948
Static Loaded Radius (mm)	930
Rolling Circumference (mm)	6021
SRI (mm)	950
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E11-106R-003474
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4	4.8
50	1500	1935	2340	2595	2740	2995	3250	3470	3650	4000	-
40	1500	1935	2340	2595	2740	2955	3250	3470	3650	4000	-
30	1605	2075	2505	2780	2935	3210	3480	3715	3910	4280	-
10	-	1860	2340	2880	3420	3960	4080	4560	5040	5520	6000

Printed on 10/12/2023 11:38

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..