

## AGRIMAX RT 945 - Especificações técnicas



### Description

AGRIMAX RT 945 foi especialmente desenvolvido para culturas em linhas: não prejudica as culturas e protege a colheita. Além disso, as extraordinárias capacidades de autolimpeza permitem a mudança rápida das operações no campo para a utilização na estrada, onde AGRIMAX RT 945 demonstra performances brilhantes. A carcaça robusta assegura uma estabilidade excelente, máxima tração e durabilidade excepcional.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador agrícola • Trator

Version	STANDARD
Type	TL
Tyre Size	380/90 R 50 (14.9 R 50)
LI/SS	151 A8/B

## Dimensions US Standard

Usa code	94037025
Section Width (inch)	15
Overall Diameter (inch)	76.9
Static Loaded Radius (inch)	35.7
Rolling Circumference (inch)	232.3
Rim Rec	W 12
Rim Alt	W 11 ; W 13
ECE	E4-106R-001487
TRA Code	R1W

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41
30	4110	5320	6550	7080	7600	-
25	4110	5320	6550	7080	7600	-
20	4410	5710	7010	7580	8150	-
5	6050	7420	9020	10500	11070	11410

Printed on 08/12/2023 18:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..