

## AGRIMAX RT 945 - Dados técnicos



### Description

AGRIMAX RT 945 foi especialmente desenvolvido para culturas em linhas: não prejudica as culturas e protege a colheita. Além disso, as extraordinárias capacidades de autolimpeza permitem a mudança rápida das operações no campo para a utilização na estrada, onde AGRIMAX RT 945 demonstra performances brilhantes. A carcaça robusta assegura uma estabilidade excelente, máxima tração e durabilidade excepcional.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador agrícola • Trator

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>420/90 R 30</b>	STANDARD	94063857	R1W	147 A8/B	DW13	W 14 L	16.5	59.8	26.9	180	TL	E11-106R-006021
<b>320/90 R 42 (12.4 R 42)</b>	STANDARD	94038664	R1W	139 A8/B	W 10	W 9 ; W 11	12.6	64.7	29.9	194.6	TL	E4-106R-000783
<b>320/90 R 46 (12.4 R 46)</b>	STANDARD	94044719	R1W	146 A8/B	W 10	W 9 ; W 11	12.6	68.7	31.9	206	TL	E4-106R-001399
<b>320/90 R 46 (12.4 R 46)</b>	STANDARD	94051694	R1W	148 D/151 A8	W 10	W 9 ; W 11	12.6	68.7	31.9	206	TL	E11-106R-004068
<b>380/90 R 46 (14.9 R 46)</b>	STANDARD	94040551	R1W	155 A8/B	W 12	W 11 ; W 13	15	72.9	34.1	222.4	TL	E4-106R-00797
<b>380/90 R 46 (14.9 R 46)</b>	STANDARD	94021833	R1W	159 A8/B	W 12	W 11 ; W 13	15	72.9	33.8	224.4	TL	E4-106R-001409
<b>320/90 R 50 (12.4 R 50)</b>	STANDARD	94037612	R1W	150 A8/B	W 10	W 9 ; W 11	12.6	72.7	34.4	221.2	TL	E4-106R-000787
<b>380/90 R 50 (14.9 R 50)</b>	STANDARD	94037025	R1W	151 A8/B	W 12	W 11 ; W 13	15	76.9	35.7	232.3	TL	E4-106R-001487
<b>380/90 R 50 (14.9 R 50)</b>	STANDARD	94065479	R1W	160A8/B	W 12	W 11 ; W 13	15.4	76.9	36.3	234.6	TL	E11-106R-006446
<b>320/90 R 54 (12.4 R 54)</b>	STANDARD	94037094	R1W	156 A8/B	W 10	W 9 ; W 11	12.6	76.7	36.6	237	TL	E11-106R-003474
<b>380/90 R 54 (14.9 R 54)</b>	STANDARD	94046799	R1W	158 A8/B	W 12	W 11 ; W 13	15	80.9	37.9	245.4	TL	E4-106R-001488

Printed on 19/04/2024 19:41

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..