

## AGRIMAX RT 955 - Especificações técnicas



### Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador agrícola • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	210/95 R 32 (8.3 R 32)
LI/SS	120 A8/B

## Dimensions International Standard

Section Width (mm)	214
Overall Diameter (mm)	1213
Static Loaded Radius (mm)	571
Rolling Circumference (mm)	3703
SRI (mm)	575
Rim Rec	W 7
Rim Alt	W 6
ECE	E4-106R-001391
TRA Code	R1

## Load capacity (Kg)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6
50	645	830	1010	1095	1190	1305	1400	-
40	645	830	1010	1095	1190	1305	1400	-
30	690	885	1080	1170	1275	1395	1500	-
10	905	1180	1430	1555	1660	1830	1975	2100

Printed on 08/12/2023 07:28

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..