

AGRIMAX RT 955 - Especificações técnicas



Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Vindimadora

| | |
|-----------|---------------------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 230/95 R 40 (9.5 R 40) |
| LI/SS | 132 A8/B |

Dimensions International Standard

| | |
|----------------------------|-----------------|
| Section Width (mm) | 228 |
| Overall Diameter (mm) | 1454 |
| Static Loaded Radius (mm) | 690 |
| Rolling Circumference (mm) | 4445 |
| SRI (mm) | 700 |
| Rim Rec | W 7 |
| Rim Alt | W 8 |
| ECE | E11-106R-004066 |
| TRA Code | R1 |

Load capacity (Kg)

| km/h / bar | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 | 4.0 | 4.4 |
|------------|-----|------|------|------|------|------|------|------|------|------|
| 50 | 820 | 1060 | 1280 | 1420 | 1500 | 1640 | 1780 | 1900 | 2000 | - |
| 40 | 820 | 1060 | 1280 | 1420 | 1500 | 1640 | 1780 | 1900 | 2000 | - |
| 30 | 880 | 1135 | 1370 | 1520 | 1605 | 1755 | 1905 | 2035 | 2140 | - |
| 10 | 930 | 1170 | 1440 | 1710 | 1980 | 2040 | 2280 | 2520 | 2760 | 3000 |

Printed on 26/04/2024 08:29

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..