

AGRIMAX RT 955 - Especificações técnicas



Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	230/95 R 48 (9.5 R 48)
LI/SS	136D/139A8

Dimensions International Standard

Section Width (mm)	238
Overall Diameter (mm)	1656
Static Loaded Radius (mm)	792
Rolling Circumference (mm)	5085
SRI (mm)	825
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-004067
TRA Code	R1

Load capacity (Kg)

km/h / bar	0.6	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
65	785	920	1190	1435	1595	1680	1840	1995	2130	2240
50	825	970	1250	1510	1675	1770	1935	2100	2240	2355
40	855	1000	1290	1560	1730	1825	1995	2165	2310	2430
30	905	1060	1370	1655	1835	1935	2120	2300	2455	2580
10	1180	1380	1785	2155	2390	2520	2760	2995	3195	3360

Printed on 28/04/2024 22:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..