

AGRIMAX RT 955 - Especificações técnicas



Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador agrícola • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	230/95 R 48 (9.5 R 48)
LI/SS	136D/139A8

Dimensions US Standard

Usa code	94052837
Section Width (inch)	9.4
Overall Diameter (inch)	65.2
Static Loaded Radius (inch)	31.2
Rolling Circumference (inch)	200.2
Rim Rec	W 8
Rim Alt	W 7
ECE	E11-106R-004067
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	17	23	29	35	41	46	52	58
40	1730	2030	2620	3160	3520	3700	4060	4400	4700	4940
30	1820	2140	2760	3330	3690	3900	4270	4630	4940	5190
25	1880	2200	2840	3440	3810	4020	4400	4770	5090	5360
20	2000	2340	3020	3650	4050	4270	4670	5070	5410	5690
5	2600	3040	3940	4750	5270	5560	6080	6600	7040	7410

Printed on 28/04/2024 22:39

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..