

## AGRIMAX RT 955 - Especificações técnicas



### Description

AGRIMAX RT 955 é um pneu radial BKT ideal para as aplicações de culturas em linhas, enquanto algumas medidas também são idóneas para a irrigação e a vindima. O desenho do piso do pneu especial com os seus ombros arredondados assegura excelentes prestações de tração, estabilidade e ótimas qualidades de autolimpeza. Graças a carcaça robusta AGRIMAX RT 955 possui uma capacidade de carga elevada.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Pulverizador agrícola • Vindimadora

Version	STANDARD
Type	TL
Tyre Size	270/95 R 32 (11.2 R 32)
LI/SS	136 A8/B

## Dimensions US Standard

Usa code	94021857
Section Width (inch)	10.8
Overall Diameter (inch)	52.2
Static Loaded Radius (inch)	24.2
Rolling Circumference (inch)	160.5
Rim Rec	W 9
Rim Alt	W 8 ; W 10
ECE	E4-106R-000776
TRA Code	R1

## Load capacity (lbs)

mph / psi	12	17	23	29	35	41	46	52	58	64
30	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
25	1930	2520	3060	3360	3560	3900	4250	4600	4930	-
20	2070	2700	3280	3600	3810	4190	4550	4930	5290	-
5	2300	2900	3560	4230	4890	5040	5630	6230	6820	7410

Printed on 26/04/2024 09:50

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..